

# MAJIC® ALL-PURPOSE SPRAY ENAMEL

#### **FEATURES**

- · Provides a hard, durable finish
- Excellent for metal, wood, concrete, plaster, masonry and hardboard

## **DESCRIPTION & USES**

Majic All Purpose Enamel Spray provides a hard, durable finish. It is an all purpose enamel - excellent for metal, wood, concrete, plaster, masonry and hardboard.

#### **PRODUCTS & SIZES**

8-22474 White, 8-22475 Red, 8-22476 Steel Gray, 8-22477 Black. Available in 10 oz sprays.

#### **SURFACE PREPARATION**

Surface must be dry and free of dirt, dust, grease or wax. Protect surrounding areas with drop cloths.

#### **APPLICATION**

Always apply paint at room temerature (70° - 80° F). To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattle. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

### **PHYSICAL PROPERTIES**

RESIN TYPE	Alkyd
SOLVENT	Refer to MSDS
VOC / MIR (sprays)	< 1.40 grams/liter
FILM THICKNESS	Mils Wet- N/A
	Mils Dry- N/A
COVERAGE	20-30 sq ft /can
DRY TIMES AT 77°F AND	1 Hour <b>To Touch</b>
<b>50% RELATIVE HUMIDITY</b>	12 Hours <b>To Recoat</b>
VISCOSITY	N/A
FLASH POINT	< 50° F
FINISH	Medium Gloss

# Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

#### Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.