

MAJIC® ALL-PURPOSE ENAMEL**FEATURES**

- Tough
- Durable
- Long lasting
- Resists scuffs, fading, cracking and peeling

DESCRIPTION & USES

Majic Oil Base All Purpose Enamel is recommended where a hard, durable interior or exterior finish is desired. It is an all purpose enamel - excellent for wood, concrete, plaster, masonry, hardboard and metal.

PRODUCTS & SIZES

Available in gallons and quarts. 8-2474 White, 8-2475 Red, 8-2476 Steel Gray, 8-2477 Black

SURFACE PREPARATION

New or previously painted surfaces must be free of moisture, dust, dirt, wax, polish and grease. Wash thoroughly and let dry completely. Rust spots on metal must be removed and spot primed. Efflorescence on masonry or concrete surfaces must be removed. Wash with a solution mixed with one pound of caustic soda to a gallon water, then rinse thoroughly to remove all traces of caustic and allow to completely dry.

APPLICATION

Stir contents thoroughly until uniform. If using two or more gallons of the same color, mix together and stir paint thoroughly to make sure color is uniform throughout. Apply smoothly and evenly with a good quality nylon brush, short nap roller or pad applicator. Do not paint exterior surfaces when temperatures are below 50° F , in direct sunlight, or if rain is expected within 24 hours. Avoid painting on hot surfaces. CAUTION: Surfaces coated with this product may become slippery when wet. DO NOT THIN.

PHYSICAL PROPERTIES

RESIN TYPE	Alkyd
SOLVENT	Mineral Spirits & Water
VOC / MIR	< 340 gm/ltr
FILM THICKNESS	4.0 Mils Wet 1.2 Mils Dry
COVERAGE	Up to 400 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	24 Hours To Touch 24 Hours To Recoat
FLASH POINT	105° F (108° F for 8-2480)
VISCOSITY	80 - 90 KU
FINISH	Medium Gloss

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.