

# **TECHNICAL DATA**

8-27962 Series

# MAJIC® GRIP-IT TEXTURED SPRAY ENAMEL

## **FEATURES**

- Heavy duty formulation
- Excellent Adhesion
- Slip Resistance for use on tool handles, rails or wherever a slip resistant finish is desired

# **DESCRIPTION & USES**

Majic Grip-It is a textured, heavy duty alkyd spray enamel specifically formulated for excellent adhesion, weathering, corrosion, and slip resistance.

# **PRODUCTS & SIZES**

8-27962 Equipment Yellow, 8-27966 Ag Green, 8-27972 IH Red, 8-27979 New Ford Blue, 8-27994 Gloss Black. Available in 11 oz sprays.

#### **SURFACE PREPARATION**

Surface must be clean and free of dirt, dust, grease or oil. Remove loose and flaking paint and rust. Prime Bare metal with Majic T&I Rust Inhibiting Gray, or Red Primer. Protect surrounding areas with drop cloths.

#### **APPLICATION**

Always apply at room temperature (70° - 80° F). To ensure uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in upright position 10 – 16 inches from the object being sprayed. Press the spray button firmly. Use steady even strokes while spraying. Several thin coats will result in a better finish than fewer heavy coats. If a clog develops, remove spray button with a twisting motion and clean in mineral spirits. DO NOT ATTEMPT TO DISLODGE CLOGS BY STICKING PINS, OR OTHER OBJECTS INTO THE CAN. Gently replace spray button with a twisting motion with the top of the can, and spray button, pointed away from you. Always clean the spray button immediately after use by turning the can upside down and pressing the spray button until no more paint comes out.

## **PHYSICAL PROPERTIES**

RESIN TYPE	Alkyd
SOLVENT	Refer to MSDS
VOC / MIR (sprays)	<0.95
FILM THICKNESS	Mils Wet- N/A
	Mils Dry- N/A
COVERAGE	Approx. 12 sq ft/can
DRY TIMES AT 77°F AND	4 Hours <b>To Touch</b>
<b>50% RELATIVE HUMIDITY</b>	24 Hours <b>To Recoat</b>
VISCOSITY	N/A
FLASH POINT	< 50° F
FINISH	Gloss

#### Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

#### Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.