

MAJIC[®] RUST KILL

Barbeque Black Enamel

FEATURES

- Durable heat resistant enamel
- Specially developed to renew and protect grills, stoves, and fireplaces
- Will not crack, bubble or peel
- Excellent brushing and leveling qualities

DESCRIPTION & USES

Rust Kill Barbeque Black Enamel is a durable, heat resistant enamel. Specially formulated to renew and protect grills, stoves and fireplaces. Maintains a good-looking, long-lasting finish that withstands heat up to 1300° F without cracking, bubbling or peeling. For interior and exterior use.

PRODUCTS & SIZES

8-6020 BBQ Black. Available in gallons and quarts.

SURFACE PREPARATION

All surfaces, new or previously painted, must be clean, dry and free of dust, dirt and grease. Remove loose, scaling paint by wire brushing, scraping or sanding. Glossy surfaces and all protected areas not exposed to normal weathering should be dulled by sanding. Remove oil residues from new metal surfaces by cleaning with rags saturated in mineral spirits. Surfaces with extensive rust or heavy oxidation should be cleaned to remove loose scale, dust and debris.

APPLICATION

The surface must be thoroughly dry. Do not apply when temperature is likely to drop below 50° F during the drying period, nor on damp or rainy days. Avoid painting on hot surfaces. Stir the paint thoroughly prior to application. To assure penetration into corners and crevices, brush or spray application is preferred. However, application with a short nap roller is satisfactory on large flat surfaces. If brushing a natural bristle brush will give best results. To assure a firm film, this product should be heat-cured. After application, allow a 2-4 hour dry period; then raise temperature of painted surface to minimum of 400° F. Raise to the normal operating temperature levels over the next 6 to 8 hours.

PHYSICAL PROPERTIES

RESIN TYPE	Silicone/ Alkyd/Petroleum
SOLVENT	Mineral Spirits VM&P Xylene
GLOSS	0-10 @60°
VOC	<650 grams/liter
FILM THICKNESS	5.0 Mils Wet
	1.3 Mils Dry
COVERAGE	Up to 500 sq. ft./gallon
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	20-30 Minutes To Touch
	12 Hours To Recoat
	7-14 Days Full Cure
VISCOSITY	53 - 60 KU
FINISH	Matte
FLASH POINT	<50°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.