

MAJIC® PROFESSIONAL Interior Latex Semi-Gloss Wall Paint

FEATURES

- Non-glare semi-gloss finish
- Low odor
- High build viscosity
- Spatter resistant
- One coat dry hide over most surfaces
- Abrasion and moisture resistant
- Soap & water clean-up

DESCRIPTION & USES

This is a good quality latex enamel for use on most interior surfaces. This finish dries to smooth soft luster that is moisture and stain resistant. One coat will hide most surfaces in good repaint condition. Professional Interior Latex Semi-Gloss Wall paint is an ideal coating for new construction, as well as general maintenance.

PRODUCTS & SIZES

8-8700 High Hiding White, 8706 White TB #1, 8707 Midtone TB # 2, 8708 Deep TB #3, 8709 Neutral TB #4. Available in gallons, quarts and 5 gallons.

SURFACE PREPARATION

The surface to be painted must be clean and free of dirt, wax, oil, grease, paste, corrosion and water-soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with an alcohol base or alkyd stain blocking primer. Satisfactory results can be obtained on most wallboard surfaces with two coats of this product. Some types of wallboard and joint compound require a good latex primer sealer for best appearances.

APPLICATION

Do not paint at surface temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3" strip at the ceiling and baseboard, round windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. For airless spray application, use a .017 to .018 reversible tip at 1,500 psi. This paint may be thinned with up to 1/2 pint water per gallon for the first coat. Do not thin the finish coat or when doing one coat work. Do not subject the finish to washing for at least 30 days. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color.

PHYSICAL PROPERTIES

RESIN TYPE	Vinyl Acrylic Latex
SOLVENT	Water
GLOSS	30-40 @ 60°
VOC	<50 grams/liter
FILM THICKNESS	3.6 Mils Wet 1.0 Mils Dry
COVERAGE	Up to 350 sq. ft./gallon
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	2 Hours To Touch Overnight Dry To Recoat 7-14 Days Full Cure
VISCOSITY	93 - 98 KU
FINISH	Semi-Gloss
FLASH POINT	> 200°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.