

**MAJIC® INTERIOR LATEX WATERPROOFING BASEMENT PAINT****FEATURES**

- Seals porous masonry with sand additives and latex resins
- Forms a moisture barrier
- Lead and mercury free

**DESCRIPTION & USES**

Majic Interior Latex Waterproofing Basement Paint forms a moisture barrier by filling in and sealing porous masonry with sand additives and latex resins. Use it on: Interior surfaces of cinder block, vertically porous concrete and cement. This product is intended for use on walls. NOTE: Not for use on floors. This product does not contain cement and is not intended for use as a repairing compound for hydraulic cement.

**PRODUCTS & SIZES**

8-9500 White. Available in gallons.

**SURFACE PREPARATION**

The surface to be painted should be clean, dry and in sound condition. Before applying this paint, make sure all traces of contamination have been removed. Masonry and Concrete: All masonry surfaces should age at least one month and poured concrete should be allowed to age for 60 days before painting. For existing surfaces, scrape off loose, peeling paint. Remove efflorescence with a wire brush. Remove mildew with a solution of one part chlorine bleach to three parts water. Protect hands and eyes while mixing and using. Repair holes, cracks or separations at wall and floor junctions where seepage is occurring or has previously occurred with hydraulic cement. If surface is crumbling, completely remove loose material and resurface before painting.

**APPLICATION**

Air temperature should be between 50° and 90° F. Stir paint thoroughly with a lifting motion. Mix all paint together in a large container. If the container is not large enough to hold all the paint at one time, then continue adding paint into the container and mixing as it is used. Use a top quality long nap roller cover and short bristle brush specifically designed for use with latex paint for best results. Using a brush, trim a 3" border along the edge of a small area. While the border is still wet, roll paint into the border. Apply generously in a "V" pattern, then roll out evenly into 3 to 4 square feet areas at a time. Work paint into pores, crevices and pinholes of the wall. Two coats are recommended to ensure complete coverage and give the best moisture protection. DO NOT THIN.

**PHYSICAL PROPERTIES**

<b>RESIN TYPE</b>	Vinyl Acrylic Latex
<b>SOLVENT</b>	Water
<b>GLOSS</b>	2-5 @ 60°
<b>VOC</b>	<100 grams/liter
<b>FILM THICKNESS</b>	4.6 Mils <b>Wet</b> 2.0 Mils <b>Dry</b>
<b>COVERAGE</b>	200 sq ft/gal
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	6 Hours <b>To Touch</b> 24 Hours <b>To Recoat</b> 7-10 Days <b>Full Cure</b>
<b>VISCOSITY</b>	110-120 KU
<b>FLASH POINT</b>	> 200°F
<b>FINISH</b>	Flat

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.