

**MAJIC® COLOR RECLAIM****FEATURES**

- Hard drying acrylic
- High Gloss finish
- Fast drying
- Color restorative

**DESCRIPTION & USES**

Majic Color ReClaim is a crystal clear acrylic high gloss finish that instantly restores many oxidized or sun-faded colors to their original color and shine. For use on painted surfaces, metal, most plastics & vinyl, fiberglass.

**PRODUCTS & SIZES**

8-20003 Crystal Clear. Available in 11 oz sprays.

**SURFACE PREPARATION**

Surface must be clean, dry and free of all dust, dirt, chalk, grease/oils, loose and peeling paint, rust or other surface contaminants that may inhibit the adhesion of Majic ReClaim. Dust, dirt & chalk may be removed by scrubbing with a phosphate free detergent & water solution - followed by a clean water rinse, and allow to dry. Loose & peeling paint should be removed by sanding, grinding or wired brush. Feather sand blunt edges of the remaining, tightly adhering paint. Remove sanding dust with tack cloth or high pressure air. Oils & grease may be removed by wiping surface with mineral spirits.

**APPLICATION**

Shake can vigorously for 1 minute prior to application, and periodically during use. Hold can in upright position at approximately 10-16" from surface. Apply ReClaim in THIN, uniform passes and allow to dry. For best results, apply 2 coats, and allow 24 hours in between coats. Apply test patch to discreet area of painted surfaces and allow to dry. Discontinue use if wrinkling or delamination occurs.

**Clean Up:** Overspray may be cleaned with acetone

**PHYSICAL PROPERTIES**

<b>RESIN TYPE</b>	Acrylic / VT Alkyd
<b>SOLVENT</b>	Refer to MSDS
<b>VOC / MIR (sprays)</b>	537 g/l
<b>SOLIDS BY VOLUME</b>	11.76%
<b>SOLIDS BY WEIGHT</b>	15.69%
<b>COVERAGE</b>	25-30 sq ft/can
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	20 Minutes <b>To Touch</b> 24 Hours <b>To Recoat</b>
<b>VISCOSITY</b>	N/A
<b>FLASH POINT</b>	< 50° F
<b>FINISH</b>	High Gloss
<b>GLOSS</b>	90+ @ 60°

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.